# ift ROSENHEIM

# **Classification Report**

Number 18-002284-PR02 (NW-A01-0203-en-01)

Owner ALUMINCO S.A.

Megali Rahi

32011 Inofita Viotias

Greece

Product Double tilt and turn casement door with opening central

meeting stile

Designation Shipping name: W4750

Details Manufacturer ALUMINCO S.A., - Inofita Viotias; Material Alumin-

ium system with thermal break; Type of opening Turn / tilt and turn; Opening direction Active casement DIN right (opening) to the inside, Inactive casement DIN left (opening) to the in-

side; Overall dimensions (W x H) 1400 mm x 2200 mm

Special features Test sequence. Material compatibility must be taken into

account. Material durability must be taken into account.

Result

Air permeability according to EN 12207:2016-12

Class: 4

Resistance to wind load according to EN 12210:2016-03

Class: C2/B2

Watertightness according to EN 12208:1999-11



Class: 3A

**ift** Rosenheim 17.08.2018

Thomas Stefan, Dipl.-Ing. (FH) Head of Testing Department Building Component Testing Thomas Krichbaumer Operating Testing Officer Building Component Testing

Thomas Wichbrumer

#### Basis \*)

EN 14351-1:2006+A2:2016-09
\*) and corresponding national versions e.g. DIN EN)

Test report: 18-002284-PR02 PB-A01-0203-en-01

#### Representation



# Instructions for use

The Evidence ("Nachweis") can be used for preparing the Declaration of Performance in accordance with the Construction Products Regulation 305/2011/EU. The results obtained apply to the direct field of application determined in Annex E of EN 14351-1.

## Validity

There is no time limit.

When using this document the upto-dateness of above basis and the conformity of the product have to be observed.

### Notes on publication

The ift-Guidance Sheet "Conditions and Guidance for the Use of ift Test Documents" applies.

Identity-Check



www.ift-rosenheim.de/ift-geprueft ID: AA1-9BF29



